

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
29 April 2004 (29.04.2004)

PCT

(10) International Publication Number
WO 2004/035993 A1

- (51) International Patent Classification⁷: F01D 15/06, 17/06
- (21) International Application Number: PCT/SE2003/001575
- (22) International Filing Date: 10 October 2003 (10.10.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 0203022-9 14 October 2002 (14.10.2002) SE
- (72) Inventor; and
(75) Inventor/Applicant (for US only): ELSMARK, Karl, Johan, Lars [SE/SE]; Ättiksvägen 6, S-132 39 Saltsjö-Boo (SE).
- (74) Agent: PANTZAR, Tord; c/o Atlas Copco Tools AB, S-105 23 Stockholm (SE).
- (81) Designated States (national): JP, US.
- (84) Designated States (regional): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).
- (30) Priority Data:
0203022-9 14 October 2002 (14.10.2002) SE
- Published:
— with international search report
- (71) Applicant (for all designated States except US): ATLAS COPCO TOOLS AB [SE/SE]; S-105 23 Stockholm (SE).
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: PNEUMATIC HIGH SPEED MOTOR WITH PRESSURE ACTIVATED SPEED GOVERNOR



(57) Abstract: A pneumatic high speed motor comprises a stator housing (10,26), a rotor (20) journaled in the stator housing (10,26), a pressure air inlet passage (33,34), a speed governor valve (28-31) shiftable between an open position and a closed position for controlling the pressure air flow through the pressure air inlet passage (33,34), and a spring (38) arranged to continuously bias the speed governor valve (28-31) in the direction of the open position, wherein an air compressor (46) is driven by the rotor (20) and delivers a speed responsive output pressure, the speed governor valve (28-31) includes a valve element (29) with an activating surface (44) acted upon by the output pressure of the air compressor (46), thereby accomplishing a shifting of the speed governor valve (28-31) in the direction of the closed position against the bias force of the spring (38) at rotor speed levels exceeding a desired operating speed level.

Pneumatic high speed motor with pressure activated speed governor.

The invention relates to a pneumatic high speed motor provided with a pressure air inlet flow controlling speed governor valve as stated in the claims.

A problem concerned with speed control of high speed motors, for instance air turbines, is that mechanical speed governors are difficult to get to operate properly at high speed levels due to high dynamic forces, balancing problems etc.

One way of solving this problem is described in US Patent 5,314,299 wherein the rotation speed of a power tool air turbine is governed by a pressure air inlet flow controlling valve which is activated by the air pressure in a pressure sensing opening in the turbine stator. A co-operation between the pressure sensing opening and an oppositely located idle running nozzle in the turbine stator results in a speed responsive activation pressure to be applied on the air inlet flow controlling valve. This previously known device is less advantageous in that it is difficult to obtain an accurate enough control of the motor speed level.

The main object of the invention is to provide a pneumatic high speed motor with a pressure controlled speed governor coping with high speed operation and giving an improved speed control accuracy.

Another object of the invention is to provide a pneumatic high speed motor with an improved speed governor enabling a simple and compact motor design.

Further objects and advantages of the invention will appear

Alternative embodiments of the invention are below described in detail with reference to the accompanying drawings.

In the drawings

Fig. 1 shows a longitudinal section through a motor according to one embodiment of the invention.

Fig. 2 shows an end view of the stator housing and the governor valve assembly.

Fig. 3 shows a fractional view along line III-III in Fig. 2 illustrating an air supply passage through the stator housing.

The turbine motor illustrated in the drawing figures comprises a stator housing 10 which at its one end is rigidly secured to a transmission casing 11 supporting a drive spindle 12 via two spindle bearings 13,14. At its opposite end the stator housing 10 is connected to a support and pressure air inlet housing 16 including a pressure air inlet chamber 17 communicating with a pressure air source via a suitable conduit connection (not shown). Exhaust air from the motor is vented through a lateral outlet opening 15.

A turbine rotor 20 is journaled in the stator housing 10 via the bearings 13,14 and has a concentric socket portion 21 for connection to the drive spindle 12. The rotor 20 carries a circumferential row of drive blades 22 to be acted upon by pressure air as described below.

For dealing with the axial load acting on the rotor 20 during operation, there is provided a magnetic type thrust bearing which provides not only an extremely low frictional resistance between the rotor 20 and the housing 10 but also a large load transferring capacity in relation to its physical dimensions. The magnetic thrust bearing comprises

two magnetic discs 23,24 which are arranged to act repellant on each other to balance the axial load on the rotor 20 and keep up a clearance between them. One of the magnetic discs 23 is mounted on the rotor 20 whereas the other disc 24 is mounted on the stator housing 10.

The stator housing 10 includes a pressure air ducting stator body 26 which is provided with a circumferential row of air flow linking guide vanes 27 located concentrically with and in a close relationship to the rotor drive blades 22. The stator body 26 is formed with a valve bore 28 for guiding a movable speed governor valve element 29. The stator body 26 has radial openings 30 and 31 for communicating pressure air into and out of the valve bore 28, respectively, whereof the opening 30 communicate with a pressure air source via an inlet passage 33 in the stator housing 10, and the opening 31 communicate with the guide vanes 27 via a feed passage 34.

At the rear end of the stator housing 10 there is a socket portion 35 in which is received a lock sleeve 36. The latter is arranged to abut the against the bottom of the socket portion 35 and has an internal thread for engaging an external thread of an end cap 37 which forms an adjustable support for a bias spring 38 acting on the valve element 29. The end cap 37 is provided with an internal thread for engagement with an external thread on the stator body 26 for making the end cap 37 adjustable. The end cap 37 has a transverse slot 39 for engagement with for instance a screw driver for facilitating adjustment of the pretension of the spring 38. The lock sleeve 36 is provided with external spanner grip surfaces 41 for tightening the lock sleeve 36 against the bottom of the socket portion 35 and thereby locking the end cap 37 against unintentional rotation.

The valve element 29 comprises a waist portion 42 and an inner cylindrical portion 43 and is movable between an open position, illustrated in Fig. 1, and a closed position. The waist portion 42 always keeps the opening 30 uncovered, no matter the position of the valve element 29. In the open position of the valve element 29 the waist portion 42 provides full communication between the openings 30 and 31, but in the closed position of the valve element 29 the cylindrical portion 43 fully covers the opening 31. The bias spring 38 exerts continuously a bias force on the valve element 29 in the direction of the open position.

The valve element 29 has an inner end surface 44 defining partly an activation chamber 45 which is connected to an air compressor 46 generating a valve activating air pressure. This air compressor 46 is an axial flow type turbo compressor which comprises rotor blades 48 formed integral with a tubular neck portion 49 on the turbine rotor 20, and outlet guide vanes 50 formed on a wall element 51 mounted in the stator body 26. The compressor 46 is fed with pressure air via a feed tube 52 which extends through the stator body 26 from the pressure air inlet chamber 17 to a passage 53 in the stator body 26. This passage 53 extends to the upstream end of the rotor blades 48. Accordingly, the compressor 30 is fed with pressure air of the same pressure as the turbine rotor 20 is powered by, and the output pressure of the compressor 46 is amplified to a still higher level. The pressure amplification accomplished by the compressor is responsive to the actual speed of the motor rotor.

Moreover, the valve element 29 has an outer end surface 54 which is acted upon in the direction of the closed position of the valve element 29 by the air pressure supplied from the inlet chamber 17 via an opening 55 in the end cap 37. This means that the valve element 29 is balanced between on one hand the bias force of the spring 38 together with the

air pressure in the inlet chamber 17 acting on the end outer surface 54, and on the other hand the outlet pressure of the compressor 46 acting upon the inner end surface 44.

For enabling the pressure on the inner end surface 44 to decrease when the compressor outlet pressure and flow decreases there is provided a central passage 56 through the valve element 29 and a leak opening 57 past an end closure 58 in the passage 56. See Figs. 1 and 2.

At motor speeds exceeding a predetermined level, the activating air pressure generated by the compressor 46 is high enough to generate an activating force on the end surface 44 of the valve 29 strong enough to dominate over the bias force exerted by the spring 38. Thereby, the valve 29 will move in its closing direction, i.e. to the left in Fig. 1, to make the cylindrical portion 43 at least partly cover the opening 31 such that the air flow to the guide vanes 27 and the rotor blades 22 is reduced and the rotor speed is limited to the predetermined level.

If the rotor speed is suddenly decreased, for instance by a sudden load increase on the motor, the high compressor boosted air pressure acting on the inner valve surface 44 is able to decrease rather quickly through the passage 56 and the leak opening 57 which communicate with the air inlet chamber 17. This means that the bias spring 38 is able to move the governor valve element 29 in the opening direction to increase the motor power in response to the increased load level, thereby keeping up the speed of the rotor 20.

It is to be understood that the invention is not limited to the illustrated and described example but may be freely varied within the scope of the claims. For instance, the air compressor is not limited to the axial flow type turbo

compressor but could as well be a radial flow type turbo compressor or a screw compressor.

Likewise, the axial thrust bearing of the turbine rotor is not limited to the described magnetic type but can be a roller type bearing in such embodiments of the invention where the axial load on the turbine rotor is of a lower magnitude.

Claims.

1. Pneumatic high speed motor, comprising a stator housing (10,26), a rotor (20) journaled in said stator housing (10,26), a pressure air inlet passage (33,34), a speed governor valve (28-31) shiftable between an open position and a closed position for controlling the pressure air flow through said inlet passage (33,34), and a spring (38) arranged to continuously bias said speed governor valve (28-31) in the direction of said open position, c h a r a c t e r i z e d in that an air compressor (46) is driven by said rotor (20) and arranged to deliver a rotor speed responsive output pressure, said speed governor valve (28-31) includes a valve element (29) having an activating surface (44) exposed to the output pressure of said air compressor (46) for generating a pressure responsive activating force on said valve element (29) and accomplishing shifting of said speed governor valve (28-31) in the direction of said closed position against the bias force of said spring (38) at rotor speed levels exceeding a desired operating speed level.
2. Rotation motor according to claim 1, wherein said valve element (29) is rotation symmetric, and said activating surface (44) is formed by an end surface (44) of said valve element (29).
3. Rotation motor according to claim 1 or 2, wherein said spring (38) is pre-tensioned by a support member (37) adjustably mounted in the stator housing (10,26).
4. Rotation motor according to anyone of claims 1-3, wherein said air compressor (46) is a turbo compressor.
5. Rotation motor according to claim 4, wherein said turbo compressor (46) is an axial flow type turbo compressor.

6. Rotation motor according to claim 4 or 5, wherein said turbo compressor has a rotor integrated with said motor rotor (20).

1/1

FIG 1




FIG 2





FIG 3



BEST AVAILABLE COPY

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 03/01575

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: F01D 15/06, F01D 17/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: F01D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-INTERNAL, WPI DATA, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 6241464 B1 (HUFFAKER ET AL), 5 June 2001 (05.06.01) --	1-6
A	US 5314299 A (JACOBSSON), 24 May 1994 (24.05.94) --	1-6
A	US 4776752 A (DAVIA), 11 October 1988 (11.10.88) -- -----	1-6

☐

Further documents are listed in the continuation of Box C.

☒

See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

18 November 2003

Date of mailing of the international search report

12-01-2004

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Per-Olof Warnbo / JA A
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT
Information on patent family members

06/09/03

International application No.
PCT/SE 03/01575

Patent document cited in search report			Publication date	Patent family member(s)		Publication date
US	6241464	B1	05/06/01	GB	0014205 D	00/00/00
				GB	2355542 A,B	25/04/01
US	5314299	A	24/05/94	DE	69305424 D,T	15/05/97
				EP	0575301 A,B	22/12/93
				JP	3363206 B	08/01/03
				JP	6039745 A	15/02/94
				SE	469604 B,C	02/08/93
				SE	9201844 A	02/08/93
US	4776752	A	11/10/88	CA	1294838 A,C	28/01/92
				DE	3881453 A,T	08/07/93
				EP	0305511 A,B	08/03/89
				JP	1503079 T	19/10/89
				JP	5057401 B	24/08/93
				WO	8806676 A	07/09/88